



IA-600-LDH™

EPDM Rubber Lining / Polyester Double Jacket

INDUSTRIAL ATTACK 600 LDH™ FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns .
- Available either plain/uncoated "natural" white, or with our optional **Ultra-Shield™** high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the **Friction Fighter System™**, creating an extremely smooth waterway surface.
- The **Dura-Bond™** vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- With a higher burst strength resulting from the double jacket construction, **Industrial Attack 600 LDH™** provides more pressure capability, maneuverability and ease of handling than nitrile rubber covered single reinforcing jacket hose
- **Industrial Attack 600 LDH™** hose is a very strong and flexible hose, with good heat, abrasion and chemical resistance.

- Designed to accomplish three separate fire fighting roles, including, Attack, Relay and Supply applications as defined by NFPA 1961, requiring a higher margin of safety than is possible with nitrile covered hose

Applications include: Attack, Relay and Supply
Available in 25, 50, 75 and 100 foot lengths



HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 100' UNCLD
4"	Industrial Attack 600	600 PSI	300 PSI	4 17/32"	79 lbs.
5"	Industrial Attack 600	600 PSI	300 PSI	5 13/32"	97 lbs.

IA 600 LDH,™ Industrial Attack 600 LDH,™ Poly-Cord,™ Ultra-Shield,™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation.
All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

