



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

NAFH-187™ Type I


Polyurethane (TPU) Lining / Filament Polyester Single Jacket

NAFH-187™ Type I FEATURES

- Synthetic filament polyester warp and filler yarns are unaffected by the effects of mildew and rot, requiring less maintenance after use.
- The **Dura-Thane™** polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.
- Meets all requirements of the U.S. Forest Service Standard 5100-187 for Type I construction.
- Both the hose and couplings are made in the USA.

Applications: Forestry, Wildland and CAFS

Available in 50 and 100 foot lengths



 **FAMILY OWNED
AMERICAN MADE**

Hose will be marked "450 PSI Working Pressure" in accordance with USDA Forest Service Specification 5100-187 Type I

HOSE SIZE	SPECIFICATION NUMBER	BURST PRESSURE	WORKING PRESSURE	BOWL SIZE	WEIGHT PER 100' UNCPLD
1"	NAFH-187 I	900 PSI	450 PSI	1 ³ / ₁₆ "	9 lbs.
1 ¹ / ₂ "	NAFH-187 I	900 PSI	450 PSI	1 ¹¹ / ₁₆ "	13 lbs.

NAFH-187 Type I™ and Dura-Thane™ are trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2023A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

