NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

# IA-600 UL/FM™

## EPDM Rubber Lining / Polyester Double Jacket

### *INDUSTRIAL ATTACK-600 UL/FM™ FEATURES*

- ***Poly-Cord***™ ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available either plain / uncoated "natural" white, or with our optional ***Ultra-Shield***™ high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the ***Friction Fighter System,***™ creating an extremely smooth waterway surface, thereby reducing friction loss and improving nozzle performance.
- The ***Dura-Bond***™ vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The result is a very strong, flexible, and "Tuff" hose, with good heat and chemical resistance.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. Performance shall meet and exceed NFPA 1961

Standards.***Available in 50, 75 and 100 foot lengths***



FAMILY OWNED AMERICAN MADE

*** Available with Factory Mutual and Underwriter's Laboratories Label*

| HOSE SIZE | SPECIFICATION NUMBER | ACCEPTANCE TEST PSI | SERVICE TEST PSI | BOWL SIZE | WEIGHT PER 50' UNCPLD |
|---|---|---|---|---|---|
| 1½" | IA-600 ** | 600 PSI | 300 PSI | 1 15⁄16" | 16 lbs. |
| 2½" | IA-600 ** | 600 PSI | 300 PSI | 3" | 29 lbs. |

Industrial Attack-600 UL/FM,™ IA-600 UL/FM,™ Poly-Cord,™ Ultra-Shield,™ Friction Fighter Systerm™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2011A

**NORTH AMERICAN FIRE HOSE**
910 East Noble Way • Santa Maria, CA 93454
Tel: 805.922.7076 • Fax: 805.922.0086
**NAFHC.com**

