

The difference is...your margin of safety.

IA-800[™] EPDM Rubber Lining / Polyester Double Jacket

INDUSTRIAL ATTACK-800™ FEATURES

- **Poly-Cord**[™] ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available either plain/uncoated "natural" white, or with our optional *Ultra-Shield*[™] high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the *Friction Fighter System*,[™] creating an extremely smooth waterway surface, thereby reducing friction loss and improving nozzle performance.
- *The Dura-Bond*[™] vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The result is a very strong, flexible, and "Tuff" hose, with good heat and chemical resistance.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. Performance shall meet and exceed NFPA 1961 Standards.

Available in 50, 75 and 100 foot lengths



** Available with Factory Mutual and Underwriter's Laboratories Label



HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1"	IA-800	800 PSI	400 PSI	11⁄16"	12.5 lbs.
11⁄2"	IA-800**	800 PSI	400 PSI	1 ¹⁵ ⁄16"	16.5 lbs.
1 ¾"	IA-800	800 PSI	400 PSI	2 ³ ⁄16"	20 lbs.
2"	IA-800	800 PSI	400 PSI	2 ⁷ / ₁₆ "	21.5 lbs.
2 1⁄2"	IA-800**	800 PSI	400 PSI	3"	29.5 lbs.
3"	IA-800	800 PSI	400 PSI	3 ¹⁷ ⁄ ₃₂ "	37.5 lbs.

Industrial Attack-800,[™]IA-800,[™] Poly-Cord,[™] Ultra-Shield,[™] Friction Fighter System[™] and Dura-Bond[™] are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2020A

