



## IA-600 UL/FM<sup>™</sup>

## EPDM Rubber Lining / Polyester Double Jacket

## INDUSTRIAL ATTACK-600 UL/FM™ FEATURES

- **Poly-Cord**<sup>™</sup> ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available either plain / uncoated "natural" white, or with our optional *Ultra-Shield*<sup>™</sup> high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the *Friction Fighter System*,<sup>™</sup> creating an extremely smooth waterway surface, thereby reducing friction loss and improving nozzle performance.
- The *Dura-Bond*<sup>™</sup> vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The result is a very strong, flexible, and "Tuff" hose, with good heat and chemical resistance.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. Performance shall meet and exceed NFPA 1961

Standards. Available in 50, 75 and 100 foot lengths



## \*\* Available with Factory Mutual and Underwriter's Laboratories Label



HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	IA-600 **	600 PSI	300 PSI	1 <sup>15</sup> ⁄16"	16 lbs.
21/2"	IA-600 **	600 PSI	300 PSI	3"	29 lbs.

Industrial Attack-600 UL/FM,<sup>™</sup> IA-600 UL/FM,<sup>™</sup> Poly-Cord,<sup>™</sup> Ultra-Shield,<sup>™</sup> Friction Fighter Systerm<sup>™</sup> and Dura-Bond<sup>™</sup> are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

