



# NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

## P-500-S™

### EPDM Rubber Lining / Polyester Single Jacket

#### P-500-S™ FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns.
- The EPDM rubber lining is unaffected by Ozone deterioration.
- Available either plain / uncoated “natural” white, or with our optional **Ultra-Shield™** high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- It is designed for Emergency Fire Protection with water pressures not exceeding 225 PSI per NFPA 1961.
- Immune to the effects of mildew and rot, requiring less maintenance after use.
- The **Dura-Bond™** vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the inner jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. Performance shall meet and exceed NFPA 1961 Standards.

**Available in 50, 75 and 100 foot lengths**



\*\* Available with Factory Mutual and Underwriter's Laboratories Label

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCLD
1"	P-500-S	500 PSI	250 PSI	1 1/4"	8 lbs.
1 1/2"	P-500-S**	500 PSI	250 PSI	1 3/4"	11 lbs.
2"	P-500-S	500 PSI	250 PSI	2 5/16"	15 lbs.
2 1/2"	P-500-S**	500 PSI	250 PSI	2 13/16"	21 lbs.

P-500-S,™ Ultra-Shield,™ Poly-Cord,™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

### NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

