



Occupant Rack Hose (PR-500™)

Polyurethane (TPU) Lining / Filament Polyester Single Jacket

OCCUPANT RACK HOSE (PR-500™) FEATURES:

- Synthetic filament polyester wrap and filler yarns are unaffected by the effects of mildew and rot, requiring less maintenance after use.
- The **Dura-Thane™** polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.
- It is designed for Emergency Fire Protection with water pressures not exceeding 225 PSI per NFPA 1961.
- **Occupant Rack Hose (PR-500™)** is intended to be used only with Listed hose racks, reels and cabinets where the specific combination of hose and rack, reel or cabinet has been investigated and found acceptable.
- Hose stored on racks or reels shall be protected from the weather and any local environmental condition potentially harmful to the hose.
- **Occupant Rack Hose (PR-500™)** is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. (Prices may vary.)
- Performance shall meet and exceed NFPA 1961 Standards.

Available in 50, 75 and 100 foot lengths



* Acceptance Test Pressure is 300 PSI for UL Labeled Product ** Available with Factory Mutual and Underwriter's Laboratories Label

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	PR-500**	500 PSI*	250 PSI	1¼"	5 lbs.

PR-500™, Ultra-Shield™, Poly-Cord™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2023A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

